## Datasheet and description



# Avide Exit Light ALU recessed with horizontal sign IP20

**Product code:** AEXITL-IP20-RE

Brand link: QR code:

**ID:** AB-190518 **Date of issue:** 2024-09-10

**Company name:** Bramcke Hungary Kft.

Company address: Kishatár utca 17., 4031 Debrecen Page: 1/3

#### **SPECIFICATIONS**

EAN code: 5999097951768

Warranty: Color:

Material:

Working temperature:

Packaging: 1/b 6/c 180/p

Certifications:

Accessories: Self-adhesive stickers

#### **TECHNICAL DETAILS**

Wattage: 1W Voltage: 3.6V

Beam angle:

Dimmability: No Lumen output: 30lm

Color temperature:

Lifetime: 50 000h

Energy class:

Type of LED: DIP

Number of LEDs:

Battery type: Ni-Cd 3-6V, 500mAh

Emergency light: 180min
Recharge time: 24h
IP standard: IP20

#### **BOX PICTURE**



## Datasheet and description



# Avide Exit Light ALU recessed with horizontal sign IP20

**Product code:** AEXITL-IP20-RE

Brand link: QR code:

**ID:** AB-190518 **Date of issue:** 2024-09-10

**Company name:** Bramcke Hungary Kft.

Company address: Kishatár utca 17., 4031 Debrecen Page: 2/3

#### **PRODUCT SIZE**

Width: 365mm
Height: 100mm
Depth: 238mm

#### **CARDBOARD BOX**

EAN: 5999097951768 Packaging: 1/b 6/c 180/p

Dimensions:

Net weight: 416g Gross weight: 485g

#### **CARTON**

EAN: 5999097951775 Packaging: 1/b 6/c 180/p

Dimensions:

Net weight: 2.496kg Gross weight: 2.91kg

#### **PALLET EXAMPLE**

Height:

Width: 120cm (std Euro pallet)

Mepth: 80cm (std Euro pallet)


Cartons per pallet: 30carton/pallet

Cartons per row:

Net weight: 74.88kg Gross weight: 87.3kg

#### **PRODUCT PICTURE**

#### **PRODUCT OUTLINE**



### Datasheet and description



### Avide Exit Light ALU recessed with horizontal sign IP20

**Product code:** AEXITL-IP20-RE

Brand link: QR code:

**ID:** AB-190518 **Date of issue:** 2024-09-10

**Company name:** Bramcke Hungary Kft.

**Company address:** Kishatár utca 17., 4031 Debrecen **Page:** 3/3

#### PRODUCT DESCRIPTION

The Avide LED exit light is an edge-lit product with adhesive pictograms and 1 W output providing constant light. Back-up time in the case of a power failure is 180 minutes.

It can be mounted in four different ways (the sign can be mounted on the wall and ceiling alike and can also be rotated 90 °).

- suspended from a chain (80 cm)
- mounted on the ceiling
- mounted on a vertical wall in two different ways. Note that the product may also be mounted laterally with the set provided!

<u>Contents of the box</u>: light fixture, clear acrylic sheet, lateral mounting kit, 80 cm suspension chain, two types (horizontal, 45°) of direction indicating arrows, pictograms with figure running to the right and left, complete instructions for use and installation in English and Hungarian.