## Datasheet and description



# Avide LED T5 Integrated Tube Connector Cable

**Product code:** ABT5-CON

**Brand link:** avidelighting.com/qr/ABT5-CON

**ID:** AB-190518

**Company name:** Bramcke Hungary Kft.

Company address: Kishatár utca 17., 4031 Debrecen

QR code:

**Date of issue:** 2024-09-10

Page: 1/3

### **SPECIFICATIONS**

EAN code: 5999097909967

Warranty: 2year(s)

Working temperature:

Packaging: 1/b
Certifications: CE

## **TECHNICAL DETAILS**

Wattage:

Voltage: 220-240V

Beam angle:

Dimmability: No

Lumen output:

Color temperature:

Lifetime:

Energy class:

Type of LED: SMD IP standard: IP20

## PRODUCT PICTURE



## Datasheet and description



## Avide LED T5 Integrated Tube Connector Cable

Product code: ABT5-CON

**Brand link:** avidelighting.com/qr/ABT5-CON

**ID:** AB-190518

**Company name:** Bramcke Hungary Kft.

Company address: Kishatár utca 17., 4031 Debrecen



Date of issue: 2024-09-10

Page: 2/3

### **PRODUCT SIZE**

Diameter:

Length: 150mm

#### **CARDBOARD BOX**

EAN: 5999097909967

Packaging: 1/b

Dimensions: 180mm x 10mm x 30mm

Net weight: 37g Gross weight: 44g

#### **CARTON**

EAN: 5999097909974

Packaging: 1/b

Dimensions:

Net weight: 0.037kg
Gross weight: 0.044kg

### **PALLET EXAMPLE**

Height:

Width: 120cm (std Euro pallet)

Mepth: 80cm (std Euro pallet)

Cartons per pallet: 1carton/pallet

Cartons per row:

Net weight: 0.037kg
Gross weight: 0.044kg

### **PRODUCT PICTURE**



### **PRODUCT OUTLINE**

## Datasheet and description



## Avide LED T5 Integrated Tube Connector Cable

Product code: ABT5-CON

**Brand link:** avidelighting.com/qr/ABT5-CON

**ID:** AB-190518

**Company name:** Bramcke Hungary Kft.

Company address: Kishatár utca 17., 4031 Debrecen



**Date of issue:** 2024-09-10

**Page:** 3/3

#### **PRODUCT DESCRIPTION**

The Avide LED integrated dust- and moisture-proof fixtures represent the modern versions of traditional fittings. The fixtures of different lengths replacing the tube fixtures have a built-in LED panel that guarantees energy-saving operation. In terms of the material used, the products have a break-resistant cover. Due to the IP65 protection of the fixture, it is protected from dust and moisture, thus can also be operated at places with higher exposure to dust and humidity.

The product range includes 3 different lengths and brightness levels, available in neutral white color temperature and with an opaline cover. The 60cm fixture has 20W power, while the 120 centimeter version has a 40W and the 150 centimeter type a 60W power output respectively.