Datasheet and description



Avide LED Glass Tube 9W G13 600mm CW 6400K

Product code: AB600T8-9W-CW-GL

Brand link: avidelighting.com/qr/AB600T8-9W-CW-GL

ID: AB-190518

Company name: Bramcke Hungary Kft.

Company address: Kishatár utca 17., 4031 Debrecen



Date of issue: 2024-09-10

Page: 1/3

SPECIFICATIONS

EAN code: 5999562289440

Warranty: 2year(s)
Working temperature: -20 - +40°C
Packaging: 1/b 25/c 1650/p

Certifications: CE

PRODUCT PICTURE



TECHNICAL DETAILS

Wattage: 9W

Voltage: 220-240V

Beam angle: 240°

Dimmability: No

Lumen output: 950lm

Color temperature: 6 400K

Lifetime: 20 000h

Energy class: A+

Type of LED: SMD
IP standard: IP20

Datasheet and description



Avide LED Glass Tube 9W G13 600mm CW 6400K

Product code: AB600T8-9W-CW-GL

Brand link: avidelighting.com/qr/AB600T8-9W-CW-GL

ID: AB-190518

Company name: Bramcke Hungary Kft.

Company address: Kishatár utca 17., 4031 Debrecen



Date of issue: 2024-09-10

Page: 2/3

PRODUCT SIZE

Diameter: 26mm Length: 600mm

CARDBOARD BOX

EAN: 5999562289440 Packaging: 1/b 25/c 1650/p

Dimensions: 30mm x 30mm x 645mm

Net weight: 111.5g Gross weight: 120g

CARTON

EAN: 5999562289457 Packaging: 1/b 25/c 1650/p

Dimensions: 665mm x 190mm x 195mm

Net weight: 2.7875kg
Gross weight: 3kg

PALLET EXAMPLE

Height:

Width: 120cm (std Euro pallet)
Mepth: 80cm (std Euro pallet)

Cartons per pallet: 66carton/pallet


Cartons per row:

Net weight: 183.975kg Gross weight: 198kg

PRODUCT PICTURE



PRODUCT OUTLINE



Datasheet and description



Avide LED Glass Tube 9W G13 600mm CW 6400K

Product code: AB600T8-9W-CW-GL

Brand link: avidelighting.com/qr/AB600T8-9W-CW-GL

ID: AB-190518

Company name: Bramcke Hungary Kft.

Company address: Kishatár utca 17., 4031 Debrecen



Date of issue: 2024-09-10

Page: 3/3

PRODUCT DESCRIPTION

The Avide LED dust- and moisture-proof fixtures for tubes represent the energy-saving versions of traditional fittings. The fixtures of different lengths replacing the tube fixtures have a built-in LED panel that guarantees energy-saving operation. In terms of the material used, the products have a break-resistant cover. Due to the IP65 protection of the fixture, it is protected from dust and moisture, thus can also be operated at places with higher exposure to dust and humidity.

The product range includes a 1 and 2 LED design, in lengths of 0.6, 1.2 and 1.5 meter lengths, with a transparent cover.

OUR IP protected fixture category includes numerous additional products. Learn more about these on the following link.